

## 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 **Proprietary Product:** Fiberglass-reinforced luxury resilient sheet vinyl. Suitable for Residential environments.

### 1.2 Manufacturer:

Tarkett North America Phone: (800) 899-8916  
30000 Aurora Rd. (440) 543-8916  
Solon, Ohio 44139  
Web: [www.tarketthome.com](http://www.tarketthome.com)

### 1.3 Proprietary Product Description:

1.3.1 **Construction:** Luxury resilient sheet vinyl made from ortho-phthalate free, virgin raw materials.

### 1.3.2 Characteristics:

- **Construction:** Urethane Topcoat Sealed (Low Gloss)
- **Series:** 87000
- **Overall Thickness:** 0.120" (3.05 mm)
- **Wearlayer Thickness:** 0.016" (0.406 mm)
- **Width:** 12' (3.6 m)
- **Standard Roll Size:** 100 yd<sup>2</sup> (83.6 m<sup>2</sup>)
- **Weight per Square Yard:** 4.03 lbs (1.83 kg)

## 2. PRODUCT DETAILS AND TECHNICAL DATA

2.1 **Sheet Material:** ASTM F1303 Type 1, Grade 2, Class C

2.2 **Slip Resistance:** ASTM D2047 >0.5

2.3 **Flexibility:** ASTM F137 ¼"(6.4 mm)

2.4 **Stain Resistance:** ASTM F925 Passes

2.5 **Static Load Limit:** ASTM F970 125 lbs./in<sup>2</sup> (8.8 kg/cm<sup>2</sup>)

2.6 **Heat Stability:** ASTM F1514 ΔE<8

2.7 **Light Stability:** ASTM F1515 ΔE<8

2.8 **Sound Reduction:** ASTM E2179 ΔIIC 22

2.9 **Fire Performance:** ASTM E648 >0.45 W/cm<sup>2</sup>

2.10 **Smoke Density:** ASTM E662 <450

2.11 **HUD/FHA Minimum Property Standards:** Meets Wearlayer Thickness

2.12 **FloorScore® Certification SCS-EC10.3-2014 v4.1:** SCS-FS-02746

2.13 **Asthma and Allergy Certified:** ASR-1155-03

## 3. INSTALLATION

See FiberFloor installation instructions found at [www.tarketthome.com](http://www.tarketthome.com) for complete details.

### 3.1. Methods:

- Releasable
- Permanent
- Floating Glueless

### 3.2. Adhesive:

- **Tarkett Qbond One or Tarkett SwiftGrip**  
Releasable - Medium Nap Roller  
Permanent - 1/32" x 1/16" x 1/32" trowel

3.3. **Seam Sealer:** Tarkett DT-65 (Low Gloss)

## 4. AVAILABILITY AND COST

Available through authorized Tarkett Retailers.

## 5. MAINTENANCE

See Residential Maintenance instructions found at [www.tarketthome.com](http://www.tarketthome.com) for complete details.

## 6. TECHNICAL SERVICES

Visit us on the web at [www.tarketthome.com](http://www.tarketthome.com)

Contact Technical Support at (888) 639 8275, or E-mail [Resilient.TechnicalSupport@tarkett.com](mailto:Resilient.TechnicalSupport@tarkett.com)

## 7. WARRANTY

- LIFETIME LIMITED RESIDENTIAL WARRANTY  
AquaGuard® 2 Year "No Questions Asked" Warranty



**ORTHO-PHTHALATE  
FREE**

### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
888-639-8275

[Resilient.TechnicalSupport@tarkett.com](mailto:Resilient.TechnicalSupport@tarkett.com)  
[www.tarketthome.com](http://www.tarketthome.com)

