

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1 **Proprietary Product:** Engineered Wood flooring. Suitable for Residential & Light Commercial environments.

1.2 **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd. (440) 543-8916
Solon, Ohio 44139
Web: www.tarketthome.com

1.3 **Proprietary Product Description:**

1.3.1 **Construction:** Engineered wood flooring constructed with no added formaldehyde.

1.3.2 **Characteristics:**

- **Locking Mechanism:** Tongue and Groove
- **Edge Treatment:** Micro Bevel
- **Gloss Level:** Matte
- **Surface Texture:** Wire Brushed
- **Face Type:** 4mm Sawn
- **Nominal Thickness:** 9/16" (14.3 mm)
- **Finish:** UV Acrylic Protective Top Layer
- **Species:** European White Oak

1.3.3 **Plank Size & Packaging**

- **Plank Widths:**
 - **Almond, Biscotti, Buff, Chestnut:**
3" (76.2 mm), 9.45" (240mm), & 3" (76.2 mm) Herringbone
 - **Ash, Latte, Sepia, Taupe, Umber, & Wheat:**
3" (76.2 mm) & 9.45" (240mm)

	3" (76.2 mm)	9.45" (240mm)	3" Herringbone (76.2 mm)
Length	Varying up to 47" (1193.8 mm) Average 34" (863.6 mm)	Varying up to 86.6" (2199.6 mm) Average 65" (1651 mm)	23.62" (599.9 mm)
Ft.² per Ctn.	11.78 (1.09 m ²)	34.10 (3.17 m ²)	6.87 (0.64 m ²)
Weight per Ctn.	23.59 (10.7 kg)	68.34 (31.0 kg)	13.89 (6.3 kg)
Ctns. per Pallet	60	36	108

2. PRODUCT DETAILS AND TECHNICAL DATA

- 2.1 **Country of Origin:** Cambodia
- 2.2 **Abrasion Resistance:** (ASTM D4060) Passes
- 2.3 **Finish Adhesion:** (ASTM D3359) 5B – 0% removal
- 2.4 **Fire Resistance:** (ASTM E648) Class 1 (> 0.45 W/cm²)
- 2.5 **Static Load Limit:** (ASTM F970) 650 psi.
- 2.6 **Slip Resistance:** (ASTM D2394) Passes for flat walking surface
- 2.7 **Janka Hardness Scale:** (ASTM D1037) 1360
- 2.8 **FloorScore® Certification:** (SCS-105 V4.2 - 2023) SCS-FS-20252
- 2.9 **CARB 2 Compliant:** Passes
- 2.10 **EPA TSCA Title VI Certification:** Pass
- 2.11 **calCOMPLiant™ - Phase 2 Certification:** Passes



3. INSTALLATION

See Engineered Wood installation instructions found at www.tarketthome.com for complete details.

3.1. **Methods:**

- **Glue Down –**
 - Tarkett Home Wood Adhesive (1/8" x 1/4" x 1/4" Square Notch trowel, approx. coverage 40-50 ft² per gallon)
- **Staple:**
 - 15.5g staples not less than 1 1/2" (3.81 cm) in length
- **Nail**
 - 16g-18g cleat not less than 1 1/2" (3.81 cm) in length
 - Install using a Tongue & Groove Engineered Flooring nailer

4. AVAILABILITY AND COST

Available through Tarkett Retailers.

5. MAINTENANCE

See Residential Maintenance instructions found at www.tarketthome.com for complete details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarketthome.com

Contact Technical Support at (888) 639 8275, or E-mail Resilient.TechnicalSupport@tarkett.com

7. WARRANTY

STRUCTURAL WARRANTY:

- LIFETIME LIMITED RESIDENTIAL WARRANTY

FINISH WARRANTY:

- 25 YEAR LIMITED RESIDENTIAL
- 10 YEAR LIMITED LIGHT COMMERCIAL

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
888-639-8275

Resilient.TechnicalSupport@tarkett.com

www.tarketthome.com

