

# ProGen<sup>™</sup> Rigid Core Floating Luxury Vinyl Floors

ProGen flooring can be installed in Residential, Light Commercial, and 3 Seasons Room applications by following the recommendations outlined in the Tarkett ProGen Installation & Maintenance Instructions found at <u>www.tarkettna.com</u>

### 1. PRODUCT DETAILS

- Nominal Thickness: 0.197" (5 mm)
- Core Thickness: 0.157" (4 mm)
- Accoustical Backing: 0.039" (1 mm) IXPE
- Wearlayer Thickness: 0.020" (0.51 mm)
- Edge Treatment: Microbeveled or Painted Bevel

|                     | <b>5"x48"</b>         | <b>7"x60"</b>         | <b>7"x48"</b>         | <b>9"x24"</b>         | <b>12"x24"</b>                     |
|---------------------|-----------------------|-----------------------|-----------------------|-----------------------|------------------------------------|
|                     | (12.7x                | (17.8x                | (17.8x                | (22.9x                | (30.5x                             |
|                     | 121.9cm)              | 152.4cm)              | 121.9cm)              | 61.0cm)               | 61.0cm)                            |
| Number<br>of Styles | 5                     | 9                     | 8                     | 4                     | 5                                  |
| Planks /<br>Carton  | 16                    | 10                    | 12                    | 14                    | 14                                 |
| SQFT /              | <b>26.68</b>          | <b>29.61</b>          | <b>28.52</b>          | <b>20.96</b>          | <b>28.03</b> (2.60m <sup>2</sup> ) |
| Carton              | (2.48m <sup>2</sup> ) | (2.75m <sup>2</sup> ) | (2.65m <sup>2</sup> ) | (1.95m <sup>2</sup> ) |                                    |
| Weight /            | <b>42</b>             | <b>45</b>             | <b>44</b>             | <b>33.5</b>           | <b>45</b>                          |
| Carton              | (19.05 kg)            | (20.41kg)             | (19.96 kg)            | (15.20 kg)            | (20.41kg)                          |
| Cartons /<br>Pallet | 56                    | 40                    | 50                    | 64                    | 54                                 |

## 2. PRODUCT PERFORMANCE AND TECHNICAL DATA

- 2.1. **Dimensional Stability:** ASTM F2199: Passes
- 2.2. Heat Stability: ASTM 1514:  $\Delta E \leq 8$
- 2.3. Light Stability: ASTM F1515:  $\Delta E \le 8$
- 2.4. Residual Indentation : ASTM F1914: Passes
- 2.5. Stain Resistance: ASTM F925: Passes
- 2.6. Impact Sound: ASTM E2179: ∆IIC ≥ 21 dB
- 2.7. Slip Resistance: ASTM D2047: SCOF ≥ 0.5

#### 3. INSTALLATION & MAINTENANCE

See ProGen installation & maintenance instructions at <u>www.tarkettna.com</u> for complete details.

#### 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

#### 5. TECHNICAL SERVICES

Visit us on the web at <u>www.tarkettna.com</u> Contact Technical Support at (800) 899-8916 or E-mail: <u>Resilient.TechnicalSupport@tarkett.com</u>

#### 6. WARRANTY

For complete details, contact Tarkett Technical Services or visit <u>www.tarkettna.com</u>

- LIFETIME RESIDENTIAL LIMITED WARRANTY
- 15 YEAR LIGHT COMMERCIAL LIMITED WARRANTY
- 10 YEAR 3 SEASONS ROOM LIMITED WARRANTY



Solon, Ohio 44139 800.899.8916 info@tarkettna.com

Tarkett North America Technical Services Department 30000 Aurora Road

www.tarkettna.com